

MX 925 ELEGANT MULTIMEDIA POWERHOUSE

The MX 925 showcases a stunning 7" WVGA color display, the largest and highest-resolution display in the industry. A powerful processor and generous memory allocation, allows the MX 925 to stream media and visual promotions, driving new revenue opportunities while encouraging customer interaction.

BRILLIANT DISPLAY, ELEGANT DESIGN

- Large, 7" color screen area efficiently accommodates optional signature capture along with scrolling account activity, branding and promotional offers
- NFC/contactless enabled to support electronic wallets
- Generous touch screen and pen-like stylus for easy signature capture
- Ideal platform for a variety of value-added services, such as administering loyalty schemes, gift card issuance and top-up services
- Linux-based OS and application development environment offer powerful and simple development options

SPECIFICATIONS

| | |
|-------------------------|---|
| Processor | 400 MHz ARM11 32-bit RISC processor |
| Memory | 512MB (256MB Flash, 256MB SDRAM), Flash is field upgradable via USB or SD memory devices |
| Display | 7" WVGA (800 x 480) capacitive touch screen Corning® Gorilla® Glass technology |
| Operating System | Embedded Linux with Verifone security enhancements |
| Connectivity | Connect I/O with Ethernet 10/100BaseT, USB host/device, serial interfaces RS-232, RS 485 IBM Tailgate Wi-Fi bluetooth optional compatible with existing MX 800 Series cabling solutions |
| Audio | Full stereo standard on unit |
| Card Readers | Triple track bi-directional MSR landed smart card |
| Contactless | ISO14443 A&B MiFare ISO18092 capable EMVCo L1 and L2 certification supports major NFC/contactless schemes |
| Applications | Form Agent IBM EFT NCR EFT |
| Other Standard Features | Up to 3 SAM slots software controllable prompts stylus – field replaceable built-in graphical processor |
| Security | PCI PTS 4.0 approved |
| Power | Power pack output requirements: 12W, 12-24VDC, power pack input requirements: 100-240VAC, 50/60Hz |
| Environmental | 0° to 40° C (32° to 104° F) operating temperature -18° to +66° C (0° to 150° F) storage temperature 15% to 95% relative humidity, non-condensing |
| Physical | 56mm (2.2in) H x 218mm (8.6in) W x 230mm (9.1in) D; 0.9kg (2.0lbs) |



Promote Sales & Offers at the POS



Multi-use Screen Shows Transaction and Offers



EMV-ready Acceptance



NFC/Contactless Enabled